

Wall mounted fan coils with EC motor

IDROWALL-I



Cooling capacity: 2.0÷3.5 kW - Heating capacity:
3.0÷5.1 kW

✓ **Consumption reduced by 50% compared to the traditional motor**

✓ **3-way valve on board**

✓ **Integrated master/slave function and serial interface**

✓ **Remote control included**



Web code: IDR01

Wall mounted fan coils.

Construction features

- Heat exchanger: finned coil.
 - Fan: tangential with Inverter Brushless EC motor with continuous speed adjustment.
 - Baffle: motorised with different positions.
 - Structure: made of heat-resistant ABS polymer, RAL 9003 colour, complete with a regenerable polypropylene filter, adjustable fins and a natural condensate drain pan.
 - Unit equipped with a 3-way ON/OFF valve and resident RS485 serial interface.
 - Control: microprocessor electronic control.
- Adjustment functions: full auto, cool, dry, fan, autofan, heat.
Comfort functions: orienting, swing, timer, sleep, hot start, memory.
Remote control supplied as standard.

Separately supplied accessories

- KV2V - 2-way ON/OFF valve accessory.
Assembled on board by the installer.
- K2TF - Accessory for electrovalve use externally to the unit.
Assembled by the installer.
- KVAM - Wall mounted recessed box.

Controls supplied separately

- KWPI - Electronic panel for wall mounting installation.
 - KWPCI - Centralised electronic panel for wall mounting installation
- Power supply V230-1-50.

Technical Data

IDROWALL-I		21	31	41
❶ Total cooling capacity [EN1397]	kW	1,99	2,95	3,5
❷ Heating capacity (45°C) [EN1397]	kW	2,68	4,2	4,45
❸ Heating capacity (50°C)	kW	3,05	4,78	5,14
❹ Heating capacity (70°C) [EN1397]	kW	5,53	8,49	9
Air flow speed	m³/h	556	722	814
❺ Sound power	dB(A)	52	55	59
Sound pressure	dB(A)	43	46	50
Absorbed power	W	22	27	38
Electrical supply	V-ph-Hz	230-1-50	230-1-50	230-1-50
DIMENSIONS AND WEIGHTS		21	31	41
L - Width	mm	795	990	990
H - Height	mm	290	290	290
P - Depth	mm	230	230	230
Weight	kg	9,3	11,6	11,6

Data at the following conditions:

- ❶ Air: 27°C D.B.; 19°C W.B. - Water: 7/12°C.
- ❷ Air: 20°C - Water: 45/40°C.
- ❸ Air: 20°C - Water: 50°C, flow rate as in cooling.
- ❹ Air: 20°C - Water: 70/60°C.
- ❺ For room volume equal to 100 m³ and reverberation time = 0.5 sec.
- E Eurovent certificate performance.

RHOSS S.P.A. declines all responsibility for possible mistakes in this document and reserves the right to alter the features of their products without notice.

Rhoss S.p.A.
Via Oltre Ferrovia, 32
33033 Codroipo (UD) - Italy
tel. +39 0432 911611 - rhoss@rhoss.it
www.rhoss.it www.rhoss.com



RhossOfficial



RhossOfficialChannel



Rhoss