

Fan coils

YARDY EV3



Cooling capacity: 1.0÷8.3 kW - Heating capacity:
1.4÷11.7 kW

√ **New white RAL 9003 for versions with cabinet**

√ **New touch controls**

√ **Air'Suite biocide filter for healthier and cleaner air in indoor environments**

√ **Enhanced performance with 4-row coil**

√ **6-speed fan**

√ **Pre-fitted accessories and controls**

air'suite



Web code: YARV3 ACMEC controls: ACREG

Floor and ceiling fan coil units with cabinet for recessed wall or false ceiling installation.

Construction features

- Heat exchanger: with finned coil with left side connections reversible to the right.
- Centrifugal fan: 6 speeds, 3 of which are connected to the terminal block.
- Cabinet version structure: covering cabinet in pre-painted sheet steel, RAL9003, complete with regenerable filter, ABS polymer grilles and natural condensate drain pan.
- Recessed version structure: in galvanised sheet steel, complete with a natural condensate drain pan and regenerable filter.

Versions

- MVP - Vertical unit with cabinet equipped with lower air inlet and upper delivery for wall mounting installation or with feet on the ground.
- MVT - Vertical unit with cabinet equipped with front air inlet and upper delivery for floor installation.
- MXP - Horizontal/vertical unit with cabinet, equipped with lower air inlet and upper delivery, for ceiling installation, wall mounted or with feet on the ground.
- MXT - Horizontal/vertical unit with cabinet, equipped with front air inlet and upper delivery, for ceiling or floor installation.
- IVP - Recessed vertical unit equipped with lower air inlet and upper delivery for wall mounting installation.
- IVF - Recessed vertical unit equipped with lower air inlet and front delivery for wall mounting installation.
- IXP - Horizontal/vertical unit equipped with lower air inlet and upper delivery for false ceiling or recessed wall installation.

Construction set-ups

Type of unit
2T - Single main coil.
4T - Double main coil and additional.

ACCESSORIES

- ❖ Additional water heating coil for 4-pipe systems.
- ❖ Electrical resistance.
- ❖2 -way ON/OFF electrovalves for 2 and 4-pipe systems.
- ❖3 -way ON/OFF electrovalves for 2 and 4-pipe systems.
- ❖4-way ON/OFF electrovalves for 4-pipe systems with a single main coil.
- ❖Auxiliary condensate drain pan.
- ❖Air'Suite biocide filter.
- ❖ Electrical box for connection terminal block.
- ❖ Air inlet flange: Ø10cm or Ø12cm.
- Manual damper.
- Motorised damper.
- Back in view.
- Rear closing panel.
- Rear closing panel with grille and filter.
- Support feet with pipe cover.
- Flanged frame for duct connection.
- Frame with Air'Suite biocide filter (G2) that can be extracted in any direction.
- Delivery straight fitting.
- 90° delivery and inlet fitting.
- Telescopic outlet/inlet fitting.
- Inlet grille with filter.
- Delivery grille.

- Formwork for recessed wall or false ceiling installation.
- Aesthetic panel for wall mounted formwork, with air delivery and return grille for wall mounting installation.
- Aesthetic panel for formwork, with air inlet grille for wall mounting or ceiling installation.
- Delivery nozzle made of aluminium, with a double row of adjustable fins.
- Anti-vibration fitting for delivery/inlet duct connection.
- Intake/outlet plenum with round nozzles.

CONTROLS

STANDARD controls

For wall mounting installation

- Panel with speed and summer/winter switch.
- Panel with room thermostat, summer/winter switch, speed switch, ON/OFF valve control and electrical resistance.
- Minimum temperature thermostat (for installation on machine).
- Electronic panel with automatic summer/winter switching for 2-pipe systems.
- Electronic panel with automatic summer/winter switching and automatic speed adjustment for 2-pipe systems with electrical resistance or 4-pipe systems.
- Electronic panel with display and RS485 serial interface, semi-recessed in wall.

For on board installation (MVP and MVT versions)

- ❖Panel with speed switch.
- ❖Panel with room thermostat, summer/winter switch and speed switch.
- ❖Minimum temperature thermostat.
- ❖Panel with room thermostat, summer/winter switch, speed switch, ON/OFF valve control and electrical resistance.
- ❖Electronic panel with automatic summer/winter switching for 2-pipe systems.
- ❖Electronic panel with automatic summer/winter switching and automatic speed adjustment for 2-pipe systems with electrical resistance or 4-pipe systems.
- Interface board to control up to 4 fan coils.

Advanced LIT-TOUCH controls

- Flush LIT-Touch control panel in glossy black or pearl white for wall mounting installation.
- Wall mounted LIT-Touch remote control and receiver with air temperature probe and operation LED.
- ❖ LIT-Touch control with air temperature probe for on board installation.

For on board installation

- ❖ LIT-Touch electronic control for 2-pipe systems, with 2 pipes with electrical resistance or 4 pipes, complete with minimum water temperature probe, ON/OFF valve control and integrated master/slave function up to a total of 15 units.
- ❖ Additional board with 2 digital outputs that can be configured.
- ❖ On board air temperature probe.
- ❖ RS485 serial board for serial communication with other devices (Modbus RTU protocol).

Key: ❖ Factory fitted

- Supplied separately

Technical Data

YARDY EV3 MVP-MVT-MXP-MXT-IVP-IVF-IXP		15	20	24	25
❶ Total cooling capacity [EN1397]	kW	1,1	1,98	2,2	•E 2,5
❷ Heating capacity (45°C) [EN1397]	kW	1,38	2,26	2,36	•E 2,97
❸ Heating capacity (50°C)	kW	1,59	2,65	2,78	•E 3,47
❹ Heating capacity (70°C) [EN1397]	kW	2,74	4,52	4,71	• 5,94
❺ Heating capacity of additional coil (65°C) [EN1397]	kW	1,37	2,09	1,78	•E 2,7
❻ Heating capacity of additional coil (70°C) [EN1397]	kW	1,49	2,37	2,01	•E 3,06
Air flow speed	m³/h	229	339	339	• 484
Sound power	dB(A)	46	48	48	•E 48
Sound pressure	dB(A)	37	39	39	• 39
Absorbed power	W	40	40	41	•E 56
Electrical supply	V-ph-Hz	230-1-50	230-1-50	230-1-50	230-1-50

DIMENSIONS AND WEIGHT		15	20	24	25
L - MXP-MXT-MVP-MVT width	mm	700	800	800	1000
L - IVP-IXP-IVF width	mm	450	550	550	750
H - MXP-MXT-MVP-MVT height	mm	570	570	570	570
H - IVP-IXP-IVF height	mm	545	545	545	545
MVP-MVT-MXP-MXT Feet height	mm	100	100	100	100
P - MXP-MXT-MVP-MVT Depth	mm	220	220	220	220
P - IVP-IXP-IVF Depth	mm	212	212	212	212
MXP-MXT-MVP-MVT Weight	kg	16	20	20,5	20
IVP-IXP-IVF Weight	kg	14,5	16,5	17	20,5

YARDY EV3 MVP-MVT-MXP-MXT-IVP-IVF-IXP		30	34	40	45
❶ Total cooling capacity [EN1397]	kW	3,21	3,28	•E 3,72	4,26
❷ Heating capacity (45°C) [EN1397]	kW	3,59	3,77	•E 4,37	4,68
❸ Heating capacity (50°C)	kW	4,21	4,42	•E 5,11	5,51
❹ Heating capacity (70°C) [EN1397]	kW	7,17	7,54	• 8,75	9,34
❺ Heating capacity of additional coil (65°C) [EN1397]	kW	3,2	3,05	•E 3,68	3,5
❻ Heating capacity of additional coil (70°C) [EN1397]	kW	3,62	3,45	•E 4,18	3,98
Air flow speed	m³/h	547	547	• 676	681
Sound power	dB(A)	50	50	•E 51	52
Sound pressure	dB(A)	41	41	• 42	43
Absorbed power	W	60	65	•E 72	70
Electrical supply	V-ph-Hz	230-1-50	230-1-50	230-1-50	230-1-50

DIMENSIONS AND WEIGHT		30	34	40	45
L - MXP-MXT-MVP-MVT width	mm	1000	1000	1200	1200
L - IVP-IXP-IVF width	mm	750	750	950	950
H - MXP-MXT-MVP-MVT height	mm	570	570	570	570
H - IVP-IXP-IVF height	mm	545	545	545	545
MVP-MVT-MXP-MXT Feet height	mm	100	100	100	100
P - MXP-MXT-MVP-MVT Depth	mm	220	220	220	220
P - IVP-IXP-IVF Depth	mm	212	212	212	212
MXP-MXT-MVP-MVT Weight	kg	21	22	27	28
IVP-IXP-IVF Weight	kg	20,5	21,5	24	25,5

YARDY EV3 MVP-MVT-MXP-MXT-IVP-IVF-IXP		48	55	58	60
❶ Total cooling capacity [EN1397]	kW	4,76	•E 5,38	•E 5,9	•E 6,53
❷ Heating capacity (45°C) [EN1397]	kW	4,89	•E 6,13	•E 7,18	•E 7,53
❸ Heating capacity (50°C)	kW	5,79	•E 7,17	•E 8,34	•E 8,78
❹ Heating capacity (70°C) [EN1397]	kW	9,77	• 12,25	• 14,33	• 15,02
❺ Heating capacity of additional coil (65°C) [EN1397]	kW	3,34	•E 5,46	•E 5,13	•E 5,7
❻ Heating capacity of additional coil (70°C) [EN1397]	kW	3,79	•E 6,2	•E 5,81	•E 6,45
Air flow speed	m³/h	681	• 1077	• 1077	• 1235
Sound power	dB(A)	52	•E 58	•E 58	•E 62
Sound pressure	dB(A)	43	• 49	• 49	• 53
Absorbed power	W	76	•E 115	•E 145	•E 161
Electrical supply	V-ph-Hz	230-1-50	230-1-50	230-1-50	230-1-50

DIMENSIONS AND WEIGHT		48	55	58	60
L - MXP-MXT-MVP-MVT width	mm	1200	1500	1500	1500
L - IVP-IXP-IVF width	mm	950	1250	1250	1250
H - MXP-MXT-MVP-MVT height	mm	570	570	570	570
H - IVP-IXP-IVF height	mm	545	545	545	545
MVP-MVT-MXP-MXT Feet height	mm	100	100	100	100
P - MXP-MXT-MVP-MVT Depth	mm	220	220	220	220
P - IVP-IXP-IVF Depth	mm	212	212	212	212
MXP-MXT-MVP-MVT Weight	kg	29	35	35	35
IVP-IXP-IVF Weight	kg	27	34,5	34,5	34,5

YARDY EV3 MVP-MVT-MXP-MXT-IVP-IVF-IXP		74	80	88
❶ Total cooling capacity [EN1397]	kW	6,99	•E 7,82	•E 8,25
❷ Heating capacity (45°C) [EN1397]	kW	7,89	•E 8,71	•E 10,04
❸ Heating capacity (50°C)	kW	9,22	•E 10,19	•E 11,68
❹ Heating capacity (70°C) [EN1397]	kW	15,74	• 17,38	• 20,04
❺ Heating capacity of additional coil (65°C) [EN1397]	kW	5,45	•E 6,51	•E 6,27
❻ Heating capacity of additional coil (70°C) [EN1397]	kW	6,15	•E 7,36	•E 7,08
Air flow speed	m³/h	1235	• 1480	• 1480
Sound power	dB(A)	62	•E 66	•E 66
Sound pressure	dB(A)	53	• 57	• 57
Absorbed power	W	172	•E 184	•E 197
Electrical supply	V-ph-Hz	230-1-50	230-1-50	230-1-50

DIMENSIONS AND WEIGHT		74	80	88
L - MXP-MXT-MVP-MVT width	mm	1500	1500	1500
L - IVP-IXP-IVF width	mm	1250	1250	1250
H - MXP-MXT-MVP-MVT height	mm	570	570	570

H - IVP-IXP-IVF height	mm	545	545	545
MVP-MVT-MXP-MXT Feet height	mm	100	100	100
P - MXP-MXT-MVP-MVT Depth	mm	220	220	220
P - IVP-IXP-IVF Depth	mm	212	212	212
MXP-MXT-MVP-MVT Weight	kg	36	37	38
IVP-IXP-IVF Weight	kg	35,5	36,5	37,5

Data at the following conditions:

- ❶ Air: 27°C D.B.; 19°C W.B. - Water: 7/12°C.
- ❷ Air: 20°C - Water: 45/40°C.
- ❸ Air: 20°C - Water: 50°C, flow rate as in cooling.
- ❹ Air: 20°C - Water: 70/60°C.
- ❺ Air: 20°C - Water: 65/55°C.
- ❻ For room volume equal to 100 m³ and reverberation time = 0.5 sec.
 - Wired speed in terminal block.
- E Eurovent certified performance.
Yardy EV3 24 - 34 - 48 - 74 - 88 with oversized 4-row coil.
For the selection with Air'Suite filter, refer to the UP-TO-DATE selection Software.

RHOSS S.P.A. declines all responsibility for possible mistakes in this document and reserves the right to alter the features of their products without notice.

Rhoss S.p.A.
Via Oltre Ferrovia, 32
33033 Codroipo (UD) - Italy
tel. +39 0432 911611 - rhoss@rhoss.it
www.rhoss.it www.rhoss.com



RhossOfficial



RhossOfficialChannel



Rhoss